

Taihang
TAIHANG FIRE-FIGHTING

— 台杭消防 —

Taihang
TAIHANG FIRE-FIGHTING

Add: NO.807 QIANWANG STREET LIN AN CITY,ZHEJIANG PROVINCE,CHINA

Tel: 0571/63739773 0571/58611388 0571/63747868

Fax: 0571/63852178 0571/63739773 0571/63853308

FIRE-FIGHTING
CREATION.SOURCE OF MOTIVE FORCE

www.hzthfp.com



关于我们

杭州台杭防火材料有限公司，1991年创建于杭州高新技术开发区，是国内第一家从事环保型灭火器生产的中外合资企业。公司通过ISO9001:2000国际质量体系认证，历经十余年的发展，现主要生产及经营灭火器、不锈钢灭火器瓶体、CF系列阻燃剂三大系列产品。

生产的“世新”牌水基型灭火器系列产品，经过公安部消防产品合格评定中心的检验，并获得产品型式认可证书，是国家“九五”计划重点推广项目。其灭火级别高，对A、B、C类火及带电物质引起的火灾特别有效，具有强性抗复燃能力，是目前唯一通过国家检测并获得型式认可证书，能有效扑灭烃类和醇类火灾的灭火器产品（产品型号中带“AR”标记）。内充装的灭火剂，系由公安部天津消防研究所研制，我司进行开发的新型环保型药剂，其无毒、无味、无刺激、对人体无伤害，可100%生物降解，特别适合在各种人员密集的场所内配置使用，是国家环保局大力推荐产品。

不锈钢灭火器瓶体生产经过多年的钻研和积累，工艺达到国际领先水平，且具有极强的设计开发能力，可承接各种指定工艺及尺寸要求的产品开发。公司现生产有五大类多个规格的不锈钢灭火器瓶体，半数以上产品通过欧盟CE认证，产品远销韩国、日本、台湾、英国、芬兰、俄罗斯、加拿大、墨西哥等国家和地区，产品质量深受客户好评！

CF系列防火剂广泛用于木材、纸张、纺织品、化纤产品的阻燃处理，使之具有优越的防火、阻燃性能。经处理的纤维织物色泽和柔韧性无明显影响，并对天然纤维性织物还具有抵抗蛀虫的侵蚀作用。CF209系列织物防火剂，经SGS专项环保测试，不含PBB及PBDE等溴类物质及其化合物，不含卤素类及重金属物质，符合欧盟环保安全要求，经处理后的织物类产品远销德国、法国、日本等国家。

公司营销中心设在美丽富饶的山城临安市，生产基地座落于天目山国家级自然保护区，销售网络涵盖全国二十几个省市及自治区。公司拥有自营进出口权，出口销售业务经过多年的努力，已涉及五大洲多个国家和地区。凭借务实、高效的管理思想和作风，公司正着力开发更多更优的产品，以满足不同区域不同客户的需求，进一步开拓市场。全体台杭人竭诚欢迎国内外各界朋友前来公司指导和洽谈业务。



About us

HANGZHOU TAI HANG FIRE PROTECTION MATERIAL CO.,LTD was founded in 1991, located in hi-tech development zone of Hang Zhou City, Zhejiang Province. Our company covers an area of 28,000 square meters, has 15,000 square meters international standard workshop, we have complete & advanced equipment and abundant technical force and most of our equipment are imported from Germany.

We specialized in manufacturing various environmental protection fire extinguishers, at present we were Certified ISO 9001 Quality Assured Firm and extinguishers approved Europe "CE" certificate and our annual productive capacity is 1.5 million Sets of fire extinguishers.

Our company exercising the company's motto of "service in good faith", most of our fire extinguishers sell far to European market, American market and Asian market. We are well-received by vast customers both at home and abroad.

We are seeking strategic long-term partners worldwide to further develop. If your company has an interest in developing this business relations or is an OEM seeking alternate sources of high standard export products to recognized western standard then We possess the ability, QA systems to fulfill your needs.



Taihang 台杭消防
TAIHANG FIRE-FIGHTING

Brief Introduction

公司营销中心设在美丽富饶的山城临安市，生产基地坐落于天目山国家级自然保护区。销售网络涵盖全国二十几个省市及自治区，建立了一个零售、批发、大小工程以及售后维护一体化的服务网络，以给广大用户最大的便利。

我司拥有自营进出口权，出口销售业务经过多年的努力，已遍及五大洲，产品主要销往韩国、日本、台湾、澳大利亚、英国、芬兰、俄罗斯、加拿大、墨西哥、巴西等国家和地区。凭借务实、高效的管理思想和作风，公司正着力开发更多更优的产品，以满足不同区域不同的需求，进一步服务于广大客户。全体台杭人竭诚欢迎国内外各界朋友前来公司指导和洽谈业务。

National sales network covering more than two dozen cities and autonomous regions. Have exported to south Korea, Japan, Taiwan, Australia, Britain, Finland, Russia, Canada, Mexico, Brazil and other countries.

FOAM FIER EXTINGUISHER



TH-FB6

Foam fire extinguishers extinguish the fire by taking away the heat element of the fire triangle. Foam agents also separate the oxygen element from the other elements. Foam extinguishers can be used on Class A & B fires only. They are not for use on Class C fires due to the shock hazard.

FOAM FIER EXTINGUISHER



编号 PRODUCT CODE	TH-FB2	TH-FB3	TH-FB6	TH-FB9
药剂充装量 FILLING WEIGHT	2L	3L	6L	9L
药剂类型 EXTINGUISHING AGENT	FOAM	FOAM	FOAM	FOAM
瓶体直径 CYLINDER DIAMETER	108mm	130mm	153mm	180mm
总高度 OVERALL HEIGHT	415mm	428mm	580mm	620mm
总重 OVERALL WEIGHT	3.18kg	4.84kg	8.82kg	12.45kg
瓶体高度 CYLINDER HEIGHT	340mm	354mm	482mm	528mm
瓶体重量 CYLINDER WEIGHT	0.86kg	1.35kg	2.16kg	2.75kg
容积 CYLINDER VOLUME	2.69L	4.0L	8.0L	12.0L
材质牌号 STEEL PIPE	SUS304	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm
工作压力 WORKING PRESSURE	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar
测试压力 TESTING PRESSURE	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar
工作温度 OPERATING TEMP	0°C~+60°C	0°C~+60°C	0°C~+60°C	0°C~+60°C
包装数量/箱 PCS/CARTON	4 PCS/CARTON	2 PCS/CARTON	1 PCS/CARTON	1 PCS/CARTON
纸箱尺寸 CARTON SIZE	235×235×430(mm)	270×135×445(mm)	170×170×595(mm)	190×190×635(mm)
整箱毛重 GROSS WEIGHT	13.1 kg	10.2kg	9.2 kg	12.9 kg

FOAM FIER EXTINGUISHER

Taihang
TAIHANG FIRE-FIGHTING



TH-FS3

Foam fire extinguishers extinguish the fire by taking away the heat element of the fire triangle. Foam agents also separate the oxygen element from the other elements. Foam extinguishers can be used on Class A & B fires only. They are not for use on Class C fires due to the shock hazard.

FOAM FIER EXTINGUISHER



TH-FB2/FOAM



TH-FB3/FOAM



TH-FB6/FOAM



TH-FB9/FOAM

编号 PRODUCT CODE	TH-FS2	TH-FS3	TH-FS6	TH-FS9
药剂充装量 FILLING WEIGHT	2L	3L	6L	9L
药剂类型 EXTINGUISHING AGENT	FOAM	FOAM	FOAM	FOAM
瓶体直径 CYLINDER DIAMETER	108mm	130mm	153mm	180mm
总高度 OVERALL HEIGHT	425mm	442mm	585mm	625mm
总重 OVERALL WEIGHT	3.22kg	4.95kg	8.86kg	12.55kg
瓶体高度 CYLINDER HEIGHT	348mm	364mm	490mm	532mm
瓶体重量 CYLINDER WEIGHT	0.95kg	1.42kg	2.34kg	2.99kg
容积 CYLINDER VOLUME	2.69L	4.0L	8.0L	12.0L
材质牌号 STEEL PIPE	SUS304	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm
工作压力 WORKING PRESSURE	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar
测试压力 TESTING PRESSURE	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar
工作温度 OPERATING TEMP	0°C~+60°C	0°C~+60°C	0°C~+60°C	0°C~+60°C
包装数量/箱 PCS/CARTON	4 PCS/CARTON	2 PCS/CARTON	1 PCS/CARTON	1 PCS/CARTON
纸箱尺寸 CARTON SIZE	235×235×440(mm)	270×135×460(mm)	170×170×600(mm)	190×190×640(mm)
整箱毛重 GROSS WEIGHT	13.3 kg	10.5 kg	9.2 kg	12.9 kg

WATER FIER EXTINGUISHER



TH-WB6

Water fire extinguishers extinguish the fire by taking away the heat element of the fire triangle. Water extinguishers are for Class A fires only—they should not be used on Class B or C fires. The discharge stream could spread the flammable liquid in a Class B fire or could create a shock hazard on a Class C fire.



TH-WB6-WATER



TH-WW6-WATER



TH-WB9-WATER



TH-WW9-WATER

WATER FIER EXTINGUISHER

编号 PRODUCT CODE	TH-WB6	TH-WB9	TH-WW6	TH-WW9
药剂充装量 FILLING WEIGHT	6L	9L	6L	9L
药剂类型 EXTINGUISHING AGENT	WATER	WATER	WATER	WATER
瓶体直径 CYLINDER DIAMETER	153mm	180mm	180mm	180mm
总高度 OVERALL HEIGHT	574mm	615mm	535mm	602mm
总重 OVERALL WEIGHT	8.82kg	12.40kg	9.06kg	12.42kg
瓶体高度 CYLINDER HEIGHT	482mm	528mm	456mm	536mm
瓶体重量 CYLINDER WEIGHT	2.16kg	2.70kg	2.54kg	2.87kg
容积 CYLINDER VOLUME	8.0L	12L	9.2L	12.0L
材质牌号 STEEL PIPE	SUS304	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm
工作压力 WORKING PRESSURE	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar
测试压力 TESTING PRESSURE	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar
工作温度 OPERATING TEMP	0°C~+60°C	0°C~+60°C	0°C~+60°C	0°C~+60°C
包装数量/箱 PCS/CARTON	1 PCS/CARTON	1 PCS/CARTON	1 PCS/CARTON	1 PCS/CARTON
纸箱尺寸 CARTON SIZE	170×170×590(mm)	190×190×630(mm)	190×190×550(mm)	190×190×620(mm)
整箱毛重 GROSS WEIGHT	9.3 kg	12.8 kg	9.5 kg	12.8 kg

POWDER FIER EXTINGUISHER

Taihang
TAIHANG FIRE-FIGHTING



TH-PB4

Dry powder fire extinguishers extinguish the fire primarily by interrupting the chemical reaction of the fire triangle. Today's most widely used type of fire extinguisher is the multipurpose dry powder that is effective on Class A, B and C fires. This agent also works by creating a barrier between the oxygen element and the fuel element on Class A fires.



POWDER FIER EXTINGUISHER

编号 PRODUCT CODE	TH-PB2	TH-PB3	TH-PB4	TH-PB6	TH-PB9
药剂充装量 FILLING WEIGHT	2kg	3kg	4kg	6kg	9kg
药剂类型 EXTINGUISHING AGENT	50%ABC Powder	50%ABC Powder	50%ABC Powder	50%ABC Powder	50%ABC Powder
瓶体直径 CYLINDER DIAMETER	108mm	130mm	130mm	153mm	180mm
总高度 OVERALL HEIGHT	415mm	428mm	485mm	580mm	620mm
总重 OVERALL WEIGHT	3.19kg	4.84kg	5.97kg	8.78kg	12.45kg
瓶体高度 CYLINDER HEIGHT	340mm	354mm	412mm	482mm	528mm
瓶体重量 CYLINDER WEIGHT	0.86kg	1.35kg	1.51kg	2.16kg	2.75kg
容积 CYLINDER VOLUME	2.69L	4.0L	4.76L	8.0L	12.0L
材质牌号 STEEL PIPE	SUS304	SUS304	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm	1.2mm
工作压力 WORKING PRESSURE	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar
测试压力 TESTING PRESSURE	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar
工作温度 OPERATING TEMP	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C
包装数量/箱 PCS/CARTON	4 PCS/CARTON	2 PCS/CARTON	2 PCS/CARTON	1 PCS/CARTON	1 PCS/CARTON
纸箱尺寸 CARTON SIZE	235×235×430(mm)	270×135×445(mm)	270×135×500(mm)	170×170×595(mm)	190×190×635(mm)
整箱毛重 GROSS WEIGHT	13.2 kg	10.2 kg	12.4kg	9.2 kg	12.9 kg

POWDER FIER EXTINGUISHER



TH-PR4

Dry powder fire extinguishers extinguish the fire primarily by interrupting the chemical reaction of the fire triangle. Today's most widely used type of fire extinguisher is the multipurpose dry powder that is effective on Class A,B and C fires. This agent also works by creating a barrier between the oxygen element and the fuel element on Class A fires.



POWDER FIER EXTINGUISHER

编号 PRODUCT CODE	TH-PR2	TH-PR3	TH-PR4	TH-PR6	TH-PR9
药剂充装量 FILLING WEIGHT	2kg	3kg	4kg	6kg	9kg
药剂类型 EXTINGUISHING AGENT	50%ABC Powder	50%ABC Powder	50%ABC Powder	50%ABC Powder	50%ABC Powder
瓶体直径 CYLINDER DIAMETER	108mm	130mm	130mm	153mm	180mm
总高度 OVERALL HEIGHT	420mm	433mm	495mm	572mm	613mm
总重 OVERALL WEIGHT	3.19kg	4.86kg	6.06kg	8.77kg	12.46kg
瓶体高度 CYLINDER HEIGHT	345mm	360mm	420mm	492mm	536mm
瓶体重量 CYLINDER WEIGHT	0.91kg	1.42kg	1.59kg	2.29kg	2.95kg
容积 CYLINDER VOLUME	2.69L	4.0L	4.76L	8.0L	12.0L
材质牌号 STEEL PIPE	SUS304	SUS304	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm	1.2mm
工作压力 WORKING PRESSURE	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar
测试压力 TESTING PRESSURE	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar	2.5MPa/25Bar
工作温度 OPERATING TEMP	-30℃~+60℃	-30℃~+60℃	-30℃~+60℃	-30℃~+60℃	-30℃~+60℃
包装数量/箱 PCS/CARTON	4 PCS/CARTON	2 PCS/CARTON	2 PCS/CARTON	1 PCS/CARTON	1 PCS/CARTON
纸箱尺寸 CARTON SIZE	235×235×430(mm)	270×135×450(mm)	270×135×510(mm)	170×170×585(mm)	190×190×630(mm)
整箱毛重 GROSS WEIGHT	13.2 kg	10.1kg	12.5kg	9.2 kg	12.9 kg

SIMPLE FIRE EXTINGUISHER



TH-JE1

Simple fire extinguishers suit for home and car. Extinguisher the fire which happen on sofa, waste bin, oil pan, gasoline, engine of car, etc.

POWDER/FOAM FIRE EXTINGUISHER

TH-JE1-POWDER/FOAM



TH-JE2-POWDER/FOAM



TH-JE3-POWDER/FOAM



编号 PRODUCT CODE	TH-JE1	TH-JE2	TH-JE3
药剂充装量 FILLING WEIGHT	0.5kg	1kg	2kg
药剂类型 EXTINGUISHING AGENT	POWDER/FOAM	POWDER/FOAM	POWDER/FOAM
瓶体直径 CYLINDER DIAMETER	70mm	89mm	108mm
总高度 OVERALL HEIGHT	275mm	290mm	414mm
总重 OVERALL WEIGHT	1.06kg	1.72kg	3.42kg
瓶体高度 CYLINDER HEIGHT	220mm	238mm	340mm
瓶体重量 CYLINDER WEIGHT	0.40kg	0.54kg	1.11kg
容积 CYLINDER VOLUME	0.67L	1.20L	2.67L
材质牌号 STEEL PIPE	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.0mm	1.0mm	1.0mm
工作压力 WORKING PRESSURE	1.2MPa/12Bar	1.2MPa/12Bar	1.2MPa/12Bar
测试压力 TESTING PRESSURE	2.1MPa/21Bar	2.1MPa/21Bar	2.1MPa/21Bar
工作温度 OPERATING TEMP	POWDER : -30℃~+60℃	POWDER : -30℃~+60℃	POWDER : -30℃~+60℃
工作温度 OPERATING TEMP	FOAM : 0℃~+60℃	FOAM : 0℃~+60℃	FOAM : 0℃~+60℃
包装数量/箱 PCS/CARTON	12 PCS/CARTON	12 PCS/CARTON	4 PCS/CARTON
纸箱尺寸 CARTON SIZE	310×240×295(mm)	385×290×310(mm)	235×235×435(mm)
整箱毛重 GROSS WEIGHT	13.3 kg	21.2kg	14.2kg

CYLINDER



CYLINDER



编号 PRODUCT CODE	TH-WW6L	TH-WW9L	编号 PRODUCT CODE	TH-PR2L	TH-PR3L	TH-PR4L	TH-PR6L	TH-PR9L
药剂充装量 FILLING WEIGHT	6L/6-7kg	9L/9-10kg	药剂充装量 FILLING WEIGHT	2L/2kg	3L/3kg	4L/4kg	6L/6kg	9L/9-10kg
瓶体直径 CYLINDER DIAMETER	180mm	180mm	瓶体直径 CYLINDER DIAMETER	108mm	130mm	130mm	153mm	180mm
瓶体高度 CYLINDER HEIGHT	456mm	523mm	瓶体高度 CYLINDER HEIGHT	345mm	360mm	420mm	492mm	536mm
瓶体重量 CYLINDER WEIGHT	2.54kg	2.87kg	瓶体重量 CYLINDER WEIGHT	0.91kg	1.42kg	1.59kg	2.29kg	2.95kg
容量 CYLINDER VOLUME	9.2L	12.0L	容量 CYLINDER VOLUME	2.69L	4.0L	4.76L	8.0L	12.0L
瓶体材质 STEEL PIPE	SUS304	SUS304	瓶体材质 STEEL PIPE	SUS304	SUS304	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm	1.2mm
工作压力 WORKING PRESSURE20°C	1.2MPa	1.2MPa	工作压力 WORKING PRESSURE20°C	1.2MPa	1.2MPa	1.2MPa	1.2MPa	1.2MPa
测试压力 TESTING PRESSURE20°C	2.5MPa	2.5MPa	测试压力 TESTING PRESSURE20°C	2.5MPa	2.5MPa	2.5MPa	2.5MPa	2.5MPa
适合温度 OPERATING TEMP	-30°C~+60°C	-30°C~+60°C	适合温度 OPERATING TEMP	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C
包装尺寸 CARTON SIZE/mm	375×190×470	375×190×550	包装尺寸 CARTON SIZE/mm	345×230×355	275×275×375	275×275×435	320×165×510	375×190×550
包装数量 PCS/CARTON	2PCS/CARTON	2PCS/CARTON	包装数量 PCS/CARTON	6PCS/CARTON	4PCS/CARTON	4PCS/CARTON	2PCS/CARTON	2PCS/CARTON
毛重 GROSS WEIGHT	5.5kg	6.2kg	毛重 GROSS WEIGHT	5.9kg	6.1kg	6.8kg	5.0kg	6.3kg

CYLINDER

CYLINDER



编号 PRODUCT CODE	TH-FB2L	TH-FB3L	TH-FB6L	TH-FB9L	编号 PRODUCT CODE	TH-FS2L	TH-FS3L	TH-FS6L	TH-FS9L
药剂充装量 FILLING WEIGHT	2L/2kg	3L/3kg	6L/6kg	9L/9-10kg	药剂充装量 FILLING WEIGHT	2L/2kg	3L/3kg	6L/6kg	9L/9-10kg
瓶体直径 CYLINDER DIAMETER	108mm	130mm	153mm	180mm	瓶体直径 CYLINDER DIAMETER	108mm	130mm	153mm	180mm
瓶体高度 CYLINDER HEIGHT	340mm	354mm	482mm	528mm	瓶体高度 CYLINDER HEIGHT	348mm	364mm	490mm	532mm
瓶体重量 CYLINDER WEIGHT	0.86kg	1.35kg	2.16kg	2.75kg	瓶体重量 CYLINDER WEIGHT	0.95kg	1.42kg	2.34kg	2.99kg
容量 CYLINDER VOLUME	2.69L	4.0L	8.0L	12.0L	容量 CYLINDER VOLUME	2.69L	4.0L	8.0L	12.0L
瓶体材质 STEEL PIPE	SUS304	SUS304	SUS304	SUS304	瓶体材质 STEEL PIPE	SUS304	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm	材质厚度 THICKNESS OF STEEL	1.2mm	1.2mm	1.2mm	1.2mm
工作压力 WORKING PRESSURE20°C	1.2MPa	1.2MPa	1.2MPa	1.2MPa	工作压力 WORKING PRESSURE20°C	1.2MPa	1.2MPa	1.2MPa	1.2MPa
测试压力 TESTING PRESSURE20°C	2.5MPa	2.5MPa	2.5MPa	2.5MPa	测试压力 TESTING PRESSURE20°C	2.5MPa	2.5MPa	2.5MPa	2.5MPa
适合温度 OPERATING TEMP	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	适合温度 OPERATING TEMP	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C
包装尺寸 CARTON SIZE/mm	345×230×355	275×275×370	320×165×500	375×190×550	包装尺寸 CARTON SIZE/mm	345×230×355	275×275×380	320×165×505	375×190×550
包装数量 PCS/CARTON	6PCS/CARTON	4PCS/CARTON	2PCS/CARTON	2PCS/CARTON	包装数量 PCS/CARTON	6PCS/CARTON	4PCS/CARTON	2PCS/CARTON	2PCS/CARTON
毛重 GROSS WEIGHT	5.6kg	5.8kg	4.8kg	5.9kg	毛重 GROSS WEIGHT	6.1kg	6.1kg	5.1kg	6.4kg

CYLINDER



- INLET THREAD
- M24x1.5
- M30x1.5

• BOTTOM



■ 精工细琢 追求完美.....

■ 我们在意您使用的每一个细节....

■ We care about every detail.....



编号 PRODUCT CODE	TH-JE1L	TH-JE2L	TH-JE3L
药剂充装量 FILLING WEIGHT	500ml/0.5kg	900ml/1kg	2L/2kg
瓶体直径 CYLINDER DIAMETER	70mm	89mm	108mm
瓶体高度 CYLINDER HEIGHT	220mm	238mm	340mm
瓶体重量 CYLINDER WEIGHT	0.4kg	0.54kg	1.11kg
容量 CYLINDER VOLUME	0.67L	1.2L	2.67L
瓶体材质 STEEL PIPE	SUS304	SUS304	SUS304
材质厚度 THICKNESS OF STEEL	1.0mm	1.0mm	1.0mm
工作压力 WORKING PRESSURE20°C	1.2MPa	1.2MPa	1.2MPa
测试压力 TESTING PRESSURE20°C	1.8MPa	1.8MPa	1.8MPa
适合温度 OPERATING TEMP	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C
包装尺寸 CARTON SIZE/mm	300×230×235	380×290×255	345×230×355
包装数量 PCS/CARTON	12PCS/CARTON	12PCS/CARTON	6PCS/CARTON
毛重 GROSS WEIGHT	5.2kg	7.1kg	7.1kg